

5V 2 Channel relay 10A

5V 2 Channel relay 10A



2 road with light coupling relay module

Module parameters:

1. Size: 50.6 mm (length) * 38.8 mm (width) * 19.3 mm (high)
2. Weight: 30 g
3. PCB color: black
4. The board with four fixed screw holes all round, hole diameter is 3.1 mm, convenient installation and fixed
5. Loose relay, relay selection of quality single pole double throw. A common end and a beginning, a normally closed end
6. Optical coupling isolation, anti-interference performance is good
7. Low level off, released in high level. Suction state indicator right, release the state when the light is out
8. VCC for system power, JD_VCC power supply for the relays. The default 5 v relay, with jumper cap
9. Maximum output relay: 30 v / 10 a dc, ac 250 v / 10 a

Connection details:

VCC: the anode system power

The cathode GND: system power

IN1 - IN2: relay control port

Shipping list:

2 road with a light coupling relay module

Relay contact capacity 250 v10a. Relay output normally open, normally closed;

Shenzhen Rui Chi Electronics Co., Ltd.,

Low level effectively. 5 v relay signal input voltage range: 0-5 v.

The VCC power supply system. JD - VCC relay power supply. The default 5 v relay. JD - VCC and VCC short sub.

RUI CHI