



PCB LAYOUT(RECOMMENDED)  
(TOP VIEW TOL. :±0.05)

SPECIFICATION

MATERIAL  
Housing: PBT+30%G. F. UL94V-0 Color: Greyish White  
Contacts: Phosphor Bronze  
CONTACT PLATING  
TIN PLATED ON ALL OVER, Ni UNDER PLATED ALL OVER.  
ELECTRICAL  
Current rating: 15 Amps.  
Contact resistance: 30 mΩ initial  
Insulation resistance: 1000000 MΩ min @ 500 VDC  
Dielectric withstanding voltage: 3100 VAC / minute  
Operating temperature: -55° C To +125° C

Part no. A05 A - 015 F T S 0 0 0 B  
1 2 3 4 5 6 7 8 9 10

- SERIES NO.
- TYPE:  
A=Standard
- CONTACT NUMBER
- CONTACT TYPE:  
F=Female  
T=Tin
- CONTACT AREA PLATING:  
B=Greyish White
- FUNCTION OPTION:  
S=STRAIGHT
- NO USE
- NO USE
- NO USE
- INSULATOR COLOR:  
B=Greyish White

公差一览表  
TOLERANCE UNLESS OTHERWISE

X.	±0.35	X°.	±5°	单位 UNITS	770777	视图 DRAWING	管正志	产品名称 NAME	欧式大电流 15P 母座
X.	±0.30	X°.	±2°	角法 VIEW	⊙	设计 DESIGN	管正志	产品编号 PART NO.	A05A-015FTS000B
XXX	±0.25	XX°	±1°	比例 SCALE	1:1	审核 CHECKED		图号 DRAW NO	A05A-015FTS000B-A0
XXX	±0.02	XXX°	±0.5°	版本 VER	A0	核准 APPRO			
日期 DATE	2010.04.19								

