



RECOMMENDED PCB PATTERN DIM.
TOLERANCE : ±0.05

- A.Material:
 1.Insulator:High temperature thermoplastic UL94V-0,(BLACK LCP)
 2.Pho.Bronze:Plating,
 50U" MIN NICKEL UNDERPLATED;
 3-8U" GOLD ON THE CONTACT AREA;
 100U" TIN PLATING ON SOLDER TAIL
- B.Electrical specifications:
 Voltage rating: 10 V AC
 Current rating: 0.5A
 Dielectric strength: 500V AC for 1 minute min
 Insulation resistance: 1000 M ohm
 Contact resistance: 100 mill.ohm max
 Operation temperature: -25℃ to +95℃
 Product withstanding rff low soldering 260℃ for 10s
- C.Mechanical specieications:
 3.1 Durability: 5000 cycles

CUSTOMER DRAWING				一般公差 GENERAL TOLERANCE		RUI CHI						
				.X ±0.50		制图 (DR): Kevin 03/26/15'		品名(TITLE): ICA-501-006 (KSI-06211-AP) 6PI				
				.XX ±0.38		审核 (CRD):		料号 (PART NO):				
				.XXX ±0.25		版本 (REV):		比例 (SCALE):		单位 (UNITS):	张数 (SHEET):	图幅 (SIZE):
				ANGLES ±5°		A		10:1		mm	1 OF 2	A4
修订 SER	修改 REV	描述 DESCRIPTION	签名 SIGNATURE	日期 DATE	核准 (APPD):							