


## Model No. БТМ 24VDC 1A 2.1\*5.5

<p>Usage</p> 	<ul style="list-style-type: none"> <li>* LED strip, LED light, LED table lamp.</li> <li>* Router, amplifier, CCTV camera.</li> <li>* Home appliances, setup box, speaker.</li> <li>* Audio &amp; Video equipments.</li> <li>* Wireless communication electronics.</li> <li>* CD/DVD, MP3/MP4, Game player.</li> <li>* Scanner, Networking Modem, Hub Etc.</li> </ul>
Input Condition	100 to 240VAC 50/60 Hz 0.8A Max
Input Rated Voltage	100 to 240VAC
Input Voltage Range	90 to 264VAC
Input Rated Frequency	50/60Hz
Input Frequency Range	47Hz to 63Hz
Input Current	0.8A Max
Input Inrush Current	30A Max
Input No Load Power Consumption	0.1W Max At 115Vac/230Vac
Efficiency	85% Min
Rated Output Power	24W Max.
Output Voltage & Current	24V / 1A
Output Load Regulation	±5%
Dielectric Withstand Voltage	3KV 3s
Leakage Current	0.25 mA At 230Vac
Operating Temperature	0 to 40°C
Storage Temperature	-10 to 85°C
Relative Humidity	20 to 80%
Safety Protection	over current protection
	over voltage protection
	short circuit protection
	over power protection
Ripple and Noise	120mVp-p Max
Safety Standard	UL 60950
	CSA C22.2 NO.950
	TUV/VDE-EN60950
Adapter Size	80*48*33mm (L/W/H)
AC Plug	EU,US,UK,AU etc.
DC Connector	5.5*2.1*11mm (optional)
DC Cable	1m 24AWG cable (optional)
Net Weight	0.1kg/pcs
Burn-in Testing	4 hours at full load
Warranty	2 years